



SDJAS500 SDJAS1000

• Straddle legs width reach 1300mm(500kg)and1250mm(1000kgs).


Constant Cont


- Lifting Height from 1500-1600mm.
- With adjustable forged forks.
- High quality steel mast ensures rigidity and durability.
- High efficient pumps makes the control easier to operate.
- Foot and hand controlled lifting function allows the operator to work without having to perform extreme body movements.
- Metal grid protects user from lift chains.
- With safety wheel guard and brake system to ensure safety during operation.

SDJAS series with Straddle legs and adjustable forks

1 KG=2.205LB 1INCH=25.40MM

Model		SDJAS500	SDJAS1000
Load capacity/rated load	Q(kg)	500	1000
Load centre distance	c(mm)	500	500
Fork height, lowered	h ₁₃ (mm)	70	70
Height, mast lowered	h ₁ (mm)	2000	2050
Max. lift height	h ₃ (mm)	1600	1600
Height, mast extended	h ₄ (mm)	2100	2155
Overall length	l ₁ (mm)	1340/1600	1300/1560
Overall width	b ₁ (mm)	1525	1475
Fork dimensions	s/e/l(mm)	48/100/800(1060)	30/100/800(1060)
Width overall forks	b ₅ (mm)	745	950
Round clearance, laden,below mast	m ₁ (mm)	25	25
Aisle width for pallets 000x1200 crossways	A _{st} (mm)	1975	1975
Aisle width for pallets 800x1200 lengthways	A _{st} (mm)	1915	1915
Turning radius	W _a (mm)	1200	1200
Lift speed,laden/unladen	mm/time	25	25
Lowering speed,laden/unladen	mm/s	Manual control	Manual control
Service weight	kg	223	294







TEL: 0086-532-66739792 FAX: 0086-532-66739791 info@movmes.com NO.88 Chunyang Road,Chengyang, QINGDAO,CHINA www.movmes.com